



T-FLEX 913 CHESAPEAKE WATER



150 PSI MAX W.P.
(Warning: inspect hose for damage before use)

Item #	ID (inch)	OD (inch)	OD (mm)	WP PSI	WP (Bar)	BURST PSI	BURST (Bar)	HOSE WEIGHT (lbs/ft)	HOSE WEIGHT (kg/m)
GLO 913 - 100	1"	1.34	34	150	10.5	450	32	0.50	0.75
GLO 913 -125	1-1/4"	1.65	42	150	10.5	450	32	0.60	0.89
GLO 913 -150	1-1/2"	1.89	48	150	10.5	450	32	0.82	1.22
GLO 913 -200	2"	2.44	62	150	10.5	450	32	1.01	1.50
GLO 913 -300	3"	3.50	89	150	10.5	450	32	1.75	2.61
GLO 913 -400	4"	4.53	115	150	10.5	450	32	2.40	3.58
GLO 913 -600	6"	6.61	168	150	10.5	450	32	4.84	7.21
GLO 913 - 800	8"	8.66	220	100	7.0	300	21	8.10	12.07

Construction:

Tube: EPDM

Reinforcement: High-tensile synthetic textile with helical wire

Cover: EPDM, ozone & weather resistant

Operating Temperature:

-22F to +200F

Applications:

- Pumping, suction, and discharge of water, mud and slurries
- Diluted agricultural fertilizers
- Covey water

Markets:

- Construction
- Agricultural
- Equipment rental

Warning: Testing can be dangerous and should be done by trained personnel utilizing proper procedures.

Warning: Kinks can cause hose to burst causing bodily harm

Warning: Always inspect hose for defects before use. Never use a hose to transfer material it is not specifically meant to transfer. Doing so could deteriorate the hose and result in leaking, hose bursting, or end blow-offs. This could lead to serious personal injury or death.