



T-FLEX 856 TERRAPIN TANK TRUCK



150 PSI MAX W.P.
(Warning: Inspect hose for damage before use)

Item #	ID (inch)	OD (inch)	OD (mm)	WP PSI	WP (Bar)	BURST PSI	BURST (Bar)	HOSE WEIGHT (lbs/ft)	HOSE WEIGHT (kg/m)
GLO 856 -100	1"	1.38	35	150	10.5	600	42	0.51	0.76
GLO 856 -125	1-1/4"	1.65	42	150	10.5	600	42	0.75	1.12
GLO 856 -150	1-1/2"	1.93	42	150	10.5	600	42	0.93	1.38
GLO 856 -200	2"	2.48	63	150	10.5	600	42	1.10	1.64
GLO 856 -300	3"	3.5	89	150	10.5	450	32	2.30	3.42
GLO 856 - 400	4"	4.57	116	150	10.5	450	32	3.58	5.33
GLO 856 -	4"	4.61	117	150	10.5	600	42	3.76	5.60

Construction:

Tube: NBR blend

Reinforcement: High-tensile synthetic textile with helical wire and anti-static copper wire.

Cover: NBR blend, ozone & weather resistant

Operating Temperature:

-22F to +185F

Application:

- For suction and discharge of petroleum products

Markets:

- Petroleum Industry
- Oil and gas exploration
- Tank trucks
- Batch plants
- Waste hauling

Warning: Testing can be dangerous and should be done by trained personnel utilizing proper procedures.

Warning: Kinks can cause hose to burst causing bodily harm

Warning: Always inspect hose for defects before use. Never use a hose to transfer material it is not specifically meant to transfer. Doing so could deteriorate the hose and result in leaking, hose bursting, or end blow-offs. This could lead to serious personal injury or death.